



PTC30N

Professional PTZ Camera with NDI

Full HD
camera

FULL HD
1080P

30X
Optical Zoom



Management
Software



HDMI / IP /
3G-SDI



NDI

NDI HX



Professional PTZ Camera

Recording lectures and events from large seminar halls and auditoria has never been easier. The powerful lens and cutting edge 30x zoom make the PTC30N one of the most popular professional cameras in the industry. Directly stream your event from this camera once it is connected to your network.

Townhall | Auditorium | Seminar Halls | Live Events

Web: www.saatvikcommunication.com | Email info@saatvikcommunication.com

Call : +91 9313355675

Professional recording and streaming of



Events, Lectures & Seminars



Live Stream

Live stream directly from the camera without any hassles

Powerful Zoom

Designed for large seminar halls and auditoria with industry-leading 30x zoom



MAKE IN INDIA



Web: www.saativikcommunication.com | Email info@saativikcommunication.com

Call : +91 9313355675

PTC30N

SPECIFICATION



Camera	
Image Sensor	1/2.8" CMOS, 2.14MP
Focal Lens	f=4.3mm - 129.0mm
Iris	F1.6 - F4.7
Zoom	Optical: 30X, Digital: 12X
FOV	63.7°
Focus System	Auto, Manual, PTZ TriggerAF, One Push
Exposure Control	Auto, Manual, Shutter Priority, Iris Priority, Bright Priority
Shutter Speed	1/1 ~ 1/10,000s
White Balance	Auto, Manual, Indoor, Outdoor
S/N Ratio	50dB
DNR	2D/3D
WDR	Yes
BLC	Yes

PTZ	
Pan Angle/ Speed	-170° ~ +170°, 0.1° ~ 120°/S
Tilt Angle/ Speed	-30° ~ +90°, 0.1° ~ 90°/S
Presets	256
OSD	Yes
Image Flip	Yes

Network	
Resolution	Max support 1920x1080@60fps
Image Compression	H.265/H.264
Audio Compression	AAC
Protocols	ONVIF/ RTSP/ RTMP/ HTTP/ TCP/ UDP
Dual Stream	Support

Interface	
Video Output	1x3G-SDI, 1xHDMI
Audio	1xLINE IN, 1xLINE OUT
Network Interface	RJ45 (10/100M) interface, NDI
Control Interface	1xRS-232 IN, 1xRS-232 OUT, 1xRS-485 / RS-422
IR Throughout Output	1xIR throughout output

General	
Control Protocol	VISCA (Support daisy chain), PELCO-P, PELCO-D
Power	DC12V
Working Temperature	0°C ~ +40°C
Storage Temperature	-20°C ~ +60°C
Dimensions LxWxH	220mmx202mmx162mm
Screw / Mounting	Standard tripod screw hole / Wall & Ceiling
Application	Free PTZ Management Software
Weight	1.7KG

*OPTIONAL ACCESSORIES - WALL MOUNT, CEILING MOUNT, PTZ JOYSTICK CONTROLLER, CABLES

Web: www.saatvikcommunication.com | Email info@saatvikcommunication.com

Call : +91 9313355675

CONNECTING YOU **ACROSS SPACE AND TIME**